

## CERTIFICATE OF ANALYSIS

## CONTOSOL 80 (DA)

**CONTOSOL 80 (DA) is a low Aromatic hydrocarbon solvent used in various applications. This fluid is produced from carefully selected feed stocks and is free of chlorinated and glycol ether components.**

PROPERTY	METHOD	RESULT UNITS	MIN	MAX
Appearance at 25°C	VISUAL	CLEAR	CLEAR	
Density at 15°C	ASTM D4052	767.5 kg/m <sup>3</sup>	-	780
Saybolt color		+30-	+30	-
Initial boiling point (IBP)		202.2°C	REPORT	-
Final boiling point (FBP)		281.9°C	REPORT	-
Aromatics	SMS 2728	<0.05% (m/m)	-	0.1
Flash point by PMCC	ASTM D93	84.0°C	80	-
Cloud point	ASTM D2500	<-36°C	REPORT	-
Pour point	ASTM D97	<-36°C	-	-36
Kinematic Viscosity At 40 °C(104°F)	ASTM D445	1.856cst	-	1.9
Kinematic Viscosity At 25 °C(77°F)	ASTM D445	2.442mm <sup>2</sup> S	REPORT	-
Aniline POINT	ASTM D611	96.2°C	80	-

Note : \* Refer the Safety Data Sheet for safety & handling guidelines for this product.

- It is the responsibility of the user to ensure that the products are used in the applications for which they are intended and comply with all applicable laws & regulations.

**CONTINENTAL PETROLEUMS LTD.**

- The above data is indicative of recent average values minor variations which do not affect product performance or quality.
- The figures quoted are typical, do not constitute a specification and are subject to the usual manufacturing tolerances.