

CERTIFICATE OF ANALYSIS

CONTROLSOL 160 (DA)

CONTROLSOL 160 (DA) is a low Aromatic hydrocarbon solvent used in various applications. This fluid is produced from carefully selected feed stocks and is free of chlorinated and glycol ether components.

CONTROLSOL 160 (DA)

TEST	TEST METHOD	UNIT	SPEC LIMITS	RESULTS
Apperance	Visual		C & B and free From Sediments	Clear
IBP	ASTM D 86	°C	310 MIN	328
FBP			To Report	395
Density @ 15 Deg C	ASTM D 4052	Kg/m3	0.83-0.86	0.8437
Flash Point	ASTM D 93	°C	160 MIN	180
Sulfur Content	ASTM D 5453	PPM	5 MAX	<1
Aromatics	UOP 495/UV Internal Method	% Vol	0.05 MAX	ND
Saybolt Color	ASTM D 156		+30 MIN	>30
Pour Point	ASTM D 97	°C	-30 MIN	-34
Kinematic Viscosity 40 °		CST	15 MAX	13.21

FOR INDUSTRIAL APPLICATION ONLY

- | | |
|---|--|
| <ul style="list-style-type: none"> ➤ Dry Cleaning Solvent ➤ Metal Cleaning Solvent ➤ Low Odor Paint Solvent ➤ Metal Working Oil Base ➤ Cutting Oil Base ➤ Aluminum Rolling Oil Base ➤ Anti -rusting Oil Base ➤ Underbody Wax Base Oil ➤ Dewaxing Solvent ➤ Plasticizer Diluents | <ul style="list-style-type: none"> ➤ Insects Aerosol Solvent ➤ Insects Liquid Fumigator ➤ Sillicone Sealant Oil ➤ Drilling Oil ➤ Explosive Lubricating Oil ➤ Printing Ink Solvent ➤ Candle Oil ➤ Flocculant Solvent ➤ EDM Oil ➤ Textile Oil Base |
|---|--|

Note : * Refer the Safety Data Sheet for safety & handling guidelines for this product.

- It is the responsibility of the user to ensure that the products are used in the applications for which they are intended and comply with all applicable laws & regulations.

CONTINENTAL PETROLEUMS LTD.

- The above data is indicative of recent average values minor variations which do not affect product performance or quality.
- The figures quoted are typical, do not constitute a specification and are subject to the usual manufacturing tolerances.