

**Continental Petroleums Ltd.**

email : [conpetco@gmail.com](mailto:conpetco@gmail.com)

---

## **CONTROL MG 20W-50**

### **Product Description**

Control MG 20W-50 is blended from highly refined base stocks with high viscosity index and additives that impart detergent, dispersant, anti-oxidant and antiwear properties. Besides lowering the maintenance cost Control MG 20W-50 enhances the engine life with less wear and tear and controlling sludge / varnish. It provides effective protection against oxidation, wear and corrosion under high temperature operations and remains a stable multigrade. It provides cold starting and high resistance to sludge, low viscosity characteristics, low oil consumption and is fully compatible with the catalytic converters and exhaust emission control equipment.

### **Features Advantages and Potential Benefits**

- Excellent engine protection.
- Eliminates seasonal oil changes.
- Maintains a high order of engine cleanliness.
- Better control of deposit formation.
- Better oxidation stability at high temperatures.
- Excellent shear stability, maintains viscosity grade.
- Protects against rust, wear and sludge formation.
- Compatible with catalytic converters.
- Suitable for mixed fleet operation.

**Cont. on Page 2**

Continental Petroleums Ltd.

email : [conpetco@gmail.com](mailto:conpetco@gmail.com)

---

--2--

## Applications

Contol MG 20W-50 is recommended for gasoline and diesel engines passenger and commercial vehicles of every make and type, turbo charged or naturally aspirated, which require API CH4/SL quality oil.

## Specifications

Contol MG 20W-50 is recommended for use in applications requiring:  
API SL/CF, CH4 Performance levels.

**Pack Sizes** : 210 L, 50 L, 3.5 L, 3 L, 1 L, ½ L

## Typical Properties

SAE Grade	20W-50
Viscosity, ASTM D445	
cSt @40 Deg.C	169
cSt @100 Deg.C	19.2
Viscosity Index, ASTM D 2270	130
Pour Point, Deg.C, ASTM D 97	-18
Flash Point, Deg.C, ASTM D 92	240
Base Number mg KOH/g	8.4
Specific Gravity @15Deg.C, ASTM D 4052	0.894